

RICOH IM C3000 IM C3500 IM C4500 IM C6000

Full Colour Multi Function Printer

✓Copier ØPrinter ØFacsimile ØScanner

Welcome to a new era of technology that keeps your workplace up to date with RICOH IM C3000 / C3500 / C4500 / C6000 range of intelligent devices. Device and technology that is designed to grow and adapt, just as your

business does.

Today's workplace needs to be ready for tomorrow. RICOH Intelligent Devices provide smooth access to functionality upgrades and productivity enhancements when they are released, without needing to change your hardware. Turn your device into a powerful hub that helps you manage information workflows efficiently, usingtechnology that is scalable, secure, sustainable and simple.

Now is the time to:

- Protect your devices with easy access to security updates
- Take advantage of easy productivity upgrades at your own pace
- Save costs by bringing high-standard quality print output in-house
- Maximise productivity with streamlined workflows





Ricoh Outstanding Achievement in Innovation for Ricoh Intelligent Scanning

Ricoh IM C4500 Outstanding 45-ppm Colour Copier MFP

Excellent Performance with the Best Quality Output

Greater Control of Scan and Print Management

Scanning of smaller sized documents can be easily done with the new small sized paper scan unit. The double feed detection unit helps to improve scan accuracy while the EFI controller enhances print management. Now, you can also create professional grade flyers at your own convenience with our inner multi-folding unit.



Seamless User Experience

Our intelligent devices offer efficient working and reduced user intervention by expanding paper capacity. Choose from our versatile finishing and paper options for a professional touch to save time and reduce outsourcing expenses. With RICOH Intelligent Support, experience maximum device uptime and minimal disruption across all your devices.





Maximise Cost Savings

Enjoy lower running costs and reduced energy consumption thanks to environmentally friendly low TEC (Typical Electricity Consumption) values. Furthermore, take advantage of RICOH Intelligent Support services that anticipate potential issues and send corrective instructions via the Smart Operation Panel, avoiding interruptions and prolonging the optimal performance of your device – avoiding the need for intervention by more costly IT resources.



Next-level Productivity with Smart Operations

Interact with the 10.1" Smart Operation Panel like a typical smart device and configure it for quick and easy access to apps you use most often. A variety of mobile connectivity options enable printing or scanning to the office network or cloud from a smart device with built in support for NFC, AirPrint or Mopria. All this underpinned by a unique suite of support apps from RICOH Smart Integration.

RICOH IM C3000 / IM C3500 / IM C4500 / IM C6000

MAIN SPECIFICATIONS

MODEL	RICOH IM C3000	RICOH IM C3500	RICOH IM C4500	RICOH IM C6000	
GENERAL					
Warm-up Time	21 Seconds				
First Output Speed : B/W	4.5 Seconds	4.5 Seconds	3.6 Seconds	2.9 Seconds	
First Output Speed : Full Color	6.9 Seconds	6.9 Seconds	5.4 Seconds	4.2 Seconds	
Continuous Output Speed	30ppm	35ppm	45ppm	60ppm	
Memory Std/Max			4GB Max		
HDD Std/Max			Std/Max		
			· · · · · · · · · · · · · · · · · · ·		
ARDF Capacity	100 Sheets				
SPDF Capacity			heets		
Weight [Mainframe]	Less Tha		I	an 87.5Kg	
Dimensions W x D x H [Standard]	<u> </u>	587 x 685	x 788 mm		
Dimensions W x D x H [Maximum] (excluding ARDF/SPDF)		668 x 738	x 1030 mm		
Power Source		220 - 240	V 50/60Hz		
COPIER			50,00112		
			Q. Copies		
Multiple Copying		· · · · ·	9 Copies		
Resolution			dpi		
Zoom		From 25% to 4	00% in 1% Step		
PRINTER					
CPU	Intel Atom Processo	r ApolloLake 1.3GHz	Intel Atom Processo	or ApolloLake 1.6GHz	
Printer Language : Standard		PCL5c, PCL6, Postscript 3 (emu	lation), PDF direct (emulation)		
Printer Language : Option	Genu	ine Adobe® Postscript®3™, XPS, IP	DS, PictBridge, PDF Direct from A	dobe®	
Print Resolution		1,200 x	1,200 dpi		
Network Interface : Standard	Ethernet	10 base-T/100base-TX/1000 base-	r, USB Host I/F Type A, USB Device	I/F Type B	
Network Interface : Option	Ethernet 10 base-T/100base-TX/1000 base-T, USB Host I/F Type A, USB Device I/F Type B Bi-directional IEEE 1284/ECP, Wireless LAN (IEEE 802.11a/b/g/n), Additional NIC (2nd port)				
Mobile Printing Capability	Apple AirPrint™, Mopria, Google Cloud Print, NFC, Ricch Smart Device Connector				
	Windows® 7, Windows® 8.1, Windows® 10, Windows® Server 2008, Windows® Server 2008R2, Windows® Server 2012R2,				
Windows [®] environments	Windows* 7, Windows* 8.1, Windows* 10, Windows* Server 2006, Windows* Server 2006k2, Windows* Server 2012k2, Windows® Server 2016				
Mac OS environments	Macintosh OS X10.11 or Later				
UNIX environments	UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux Enterprise, IBM® AIX				
SAP [®] environments	SAP® S/4®				
Other Supported environments		IBM i	Series		
SCANNER					
Scanning Speed		120ipm (Simplex)	/ 240ipm (duplex)		
Resolution : Maximum					
Compression Method	1,200 dpi TIFF (MH, MR, MMR, JBIG2), Grayscale				
File Formats		ngle page JPEG, Single Page High Multi page PDE Multi page High (
c	Multi page PDF, Multi page High compression PDF, Multi Page PDF-A Email, Folder, USB, SD Card				
Scan Modes		Email, Folder,	USB, SD Card		
FACSIMILE					
Circuit	<u> </u>		, PBX		
Tranmission Speed	2 Seconds				
Modem Speed : Maximum	33.6 Kbps				
	8 x 3.65 line/mm, 200 x 100 dpi				
Resolution : Standard		8 x 3.65 line/mr			
Resolution : Option		16 x 15.4 line/m	n, 200 x 100 dpi		
Resolution : Option Compression Method		16 x 15.4 line/m MH, MR, I	n, 200 x 100 dpi m, 400 x 400 dpi		
Resolution : Option Compression Method Memory : Standard		16 x 15.4 line/m MH, MR, I 4MB (32	n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG 10 Pages)		
Resolution : Option Compression Method Memory : Standard Memory : Maximum		16 x 15.4 line/m MH, MR, I 4MB (32	n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG		
Resolution : Option Compression Method Memory : Standard Memory : Maximum PAPER HANDLING		16 x 15.4 line/m MH, MR, I 4MB (32 60MB (4,8	n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG 10 Pages) 800 Pages)		
Resolution : Option Compression Method Memory : Standard Memory : Maximum PAPER HANDLING Recommended Paper Size		16 x 15.4 line/m MH, MR, I 4MB (32 60MB (4,8 SRA3, A3, A4, A	n, 200 x 100 dpi m, 400 x 400 dpi VIMR, JBIG 0 Pages) 300 Pages) 5, A6, B4, B5, B6		
Resolution : Option Compression Method Memory : Standard Memory : Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std		16 x 15.4 line/m MH, MR, I 4MB (32 60MB (4,8 SRA3, A3, A4, A 1,200	n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG 0 Pages) 300 Pages) 5, A6, B4, B5, B6 Sheets		
Resolution : Option Compression Method Memory : Standard Memory : Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Input Capacity Max		16 x 15.4 line/m MH, MR, I 4MB (32 60MB (4,4 SRA3, A3, A4, A 1,200 4,700	n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG 0 Pages) 300 Pages) 5, A6, B4, B5, B6 Sheets Sheets		
Resolution : Option Compression Method Memory : Standard Memory : Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Input Capacity Max Paper Output Capacity Std		16 x 15.4 line/m MH, MR, I 4MB (32 60MB (4,8 SRA3, A3, A4, A 1,200 4,700 500 S	n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG 0 Pages) 300 Pages) 5, A6, B4, B5, B6 Sheets Sheets heets		
Resolution : Option Compression Method Memory : Standard Memory : Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Input Capacity Max Paper Output Capacity Std	1,625	16 x 15.4 line/m MH, MR, I 4MB (32 60MB (4,8 5RA3, A3, A4, A 1,200 4,700 500 S	n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG 0 Pages) 300 Pages) 5, A6, B4, B5, B6 Sheets Sheets heets 3,625	Sheets	
Resolution : Option Compression Method Memory : Standard Memory : Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Input Capacity Max Paper Output Capacity Std Paper Output Capacity Max	1,625	16 x 15.4 line/m MH, MR, I 4MB (32 60MB (4,8 5RA3, A3, A4, A 1,200 4,700 500 S	n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG 0 Pages) 300 Pages) 5, A6, B4, B5, B6 Sheets Sheets heets	Sheets	
Resolution : Option Compression Method Memory : Standard Memory : Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Input Capacity Max Paper Output Capacity Std Paper Output Capacity Max Paper Weight		16 x 15.4 line/m MH, MR, I 4MB (32 60MB (4,8 5RA3, A3, A4, A 1,200 4,700 500 S Sheets 60 - 30 paper, Special paper, Color paper,	n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG 0 Pages) 300 Pages) 5, A6, B4, B5, B6 Sheets Sheets heets heets 3,625		
Resolution : Option Compression Method Memory : Standard Memory : Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Input Capacity Max Paper Output Capacity Std Paper Output Capacity Max Paper Weight Paper Types		16 x 15.4 line/m MH, MR, I 4MB (32 60MB (4,8 5RA3, A3, A4, A 1,200 4,700 500 S Sheets 60 - 30 paper, Special paper, Color paper,	n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG 0 Pages) 300 Pages) 5, A6, B4, B5, B6 5heets 5heets 5heets 100g/m ² Letterhead, Cardstock, Preprinte		
Resolution : Option Compression Method Memory : Standard Memory : Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Input Capacity Max Paper Output Capacity Max Paper Output Capacity Max Paper Weight Paper Types ECOLOGY	Plain paper, Recycle	16 x 15.4 line/m MH, MR, I 4MB (32 60MB (4,8 SRA3, A3, A4, A 1,200 4,700 500 S Sheets 60 - 30 paper, Special paper, Color paper, Coated paper, Envelope, Gl	n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG 0 Pages) 300 Pages) 5, A6, B4, B5, B6 Sheets Sheets heets 200g/m ² Letterhead, Cardstock, Preprinte oss paper, Label paper, OHP	d paper, Bond paper,	
Resolution : Option Compression Method Memory : Standard Memory : Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Input Capacity Max Paper Output Capacity Std Paper Output Capacity Max Paper Weight Paper Types ECOLOGY Power Consumption : Max	Plain paper, Recycle Less Thar	16 x 15.4 line/m MH, MR, I 4MB (32 60MB (4,8 SRA3, A3, A4, A 1,200 4,700 500 S Sheets 60 - 30 paper, Special paper, Color paper, Coated paper, Envelope, Gl	n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG 0 Pages) 300 Pages) 5, A6, B4, B5, B6 Sheets Sheets heets 200g/m ² Letterhead, Cardstock, Preprinte oss paper, Label paper, OHP Less Tha	d paper, Bond paper, n 1,850 W	
Resolution : Standard Resolution : Option Compression Method Memory : Standard Memory : Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Output Capacity Max Paper Output Capacity Max Paper Weight Paper Types ECOLOGY Power Consumption : Max Power Consumption : Ready Power Consumption : Sleep	Plain paper, Recycle	16 x 15.4 line/m MH, MR, I 4MB (32 60MB (4,8 SRA3, A3, A4, A 1,200 4,700 500 S Sheets 60 - 30 paper, Special paper, Color paper, Coated paper, Envelope, Gl 1,700 W 5 W	n, 200 x 100 dpi m, 400 x 400 dpi MMR, JBIG 0 Pages) 300 Pages) 5, A6, B4, B5, B6 Sheets Sheets heets 200g/m ² Letterhead, Cardstock, Preprinte oss paper, Label paper, OHP Less Tha 59	d paper, Bond paper,	

RICOH IM C3000 / IM C3500 / IM C4500 / IM C6000

MAIN SPECIFICATIONS

MODEL	RICOH IM C3000	RICOH IM C3500	RICOH IM C4500	RICOH IM C6000		
OUTPUT TRAY AND FINISHER OPTION						
1 x 550-Sheets Paper Tray (PB 3270)	Paper Size : A6-SRA3, Paper Weight : 60-300g/m ²					
2 x 550-Sheets Paper Tray (PB 3280)	Paper Size : A6-SRA3, Paper Weight : 60-300g/m ²					
2,000-Sheets Large Capacity Tray (LCIT PB3290)	Paper Size : A4, Paper Weight : 60-300g/m ²					
1,500-Sheets Large Capacity Tray (LCIT RT3040)	Paper Size : A4, Paper Weight : 60-300g/m ²					
1,000-Sheets Hybrid Finisher (SR3260)	Paper Size : Proof Tray :A6-A3, Shift Tray : A6-A3, Paper weight : 60-300g/m ² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top, Bottom, 2 Staples Staple capacity Max : 50 sheets (A4) 30 Sheets (A3) Stapleless capacity Max : 5 sheets (A4/A3)					
3,000-sheet Finisher (SR 3280) [Available for IM C4500, IM C6000 only]	Paper Size : Proof Tray :A6-A3, Shift Tray : A6-A3, Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top, Bottom, 2 Staples, Top slant Staple capacity Max : 50 sheets (A4) 30 Sheets (A3)					
1,000-Sheet Booklet Finisher (SR3270)	Paper Size : Proof Tray :A6-A3, Shift Tray : A6-A3, Booklet tray : A4-A3 Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top, Bottom, 2 Staples, Booklet Staple capacity Max : 50 sheets (A4) 30 Sheets (A3)					
2,000-Sheet Booklet Finisher (SR3290) [Available for IM C4500, IM C6000 only]	Paper Size : Proof Tray :A6-A3, Shift Tray : A6-A3, Booklet tray : A4-A3 Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top, Bottom, 2 Staples, Booklet Staple capacity Max : 50 sheets (A4) 30 Sheets (A3)					
500-Sheet Internal Finisher (SR3250) (IM C6000 is not supported)	Paper Size : A6-A3, Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top, Bottom, 2 Staples Staple capacity Max : 50 sheets (A4) 30 Sheets (A3)					
250-Sheet Internal Finisher (SR3300) (Available for IM C3000, IM C3500 only)	Paper Size : A6-A3, Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top,1 Staple Staple capacity Max : 2-5 sheets (A4)					
Internal Shift Tray (SH3080)	Tray Capacity : 250 sheets, Paper size : 320 mm x 600 mm or smaller, Paper weight : 60-300g/m²					
One-bin tray (BN3130)	Tray Capacity : 125 sheets, Paper size : A5 - A3, Paper weight : 52-300g/m²					

Platen Cover PN2000, DF3110, DF3120, Fax Option Type M37, G3 Interface Unit Type M37, Fax Connection unit Type M37, FAX Memory unit Type M19 64MB, Memory Unit Type M37 4GB, Caster Table Type M3, VM Card Type M37, Side Tray, Punch Unit NA/EU/SC (PU3070,PU3080,PU3090), Internal Multi-fold unit FD3010, Camera direct print card, Postscript3 Unit Type M37, XPS direct print Option Type M37, IEEE 1284 I/F Type M19, IEEE 802.11a/g/n I/F Type M19, Device server option Type M37, File format Converter Type M19, OCR Unit Type M13, Small Paper Feeding Unit Type M37, Page Keeper Type M37, ADF Handle, External Keyboard Bracket Type M19, Optional Counter Interface Unit Type M12, Key Counter Bracket Type M3, NFC Card Reader Type M37, Smart Card Reader Built in Unit Type M37, External USB Keyboard (No bracket), Color Controller E-25C, Unicode Font Package for SAP®License.

*AirPrint certification will be available in 2019.



www.ricoh-ap.com

RICOH ASIA PACIFIC PTE LTD

103 Penang Road #08-01/07, VISIONCREST Commercial, Singapore 238467 Phone: +65 6830 5888, Fax: +65 6830 5830

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear. Copyright © 2019 Ricoh Asia Pacific Pte Ltd. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Asia Pacific Pte Ltd.



